

THE BEST-IN-CLASS ACCEPTOR—ENHANCED

mei | cashflow®
series 9500e

High-security electronic coin and token validation with advanced coin discrimination and fraud protection:

- New advanced processor to help “future-proof” the product for additional enhancements
- Best-in-class coin acceptance
 - › Automatic security algorithm
 - › Advanced coin-sensing technology
 - › Automatically adjusts to coin population
- Lowest cost of ownership
 - › MEI CASHFLOW® programming module for coin set download
 - › Easily reprogrammable for multiple countries
 - › All connection looms and configuration settings are accessible from the front
 - › Adjustments can be made without removing the unit

Complete Range of Interfaces

Serial HII | Serial ccTalk® v4.2 | Binary Coded Outputs (BCO) | Parallel

Please contact your MEI sales associate to learn how the MEI CASHFLOW® 9500e can be implemented to your coin and token validation.



mei®
www.meigroup.com

Proven performance. Increased profits.

TECHNICAL SPECIFICATIONS

- MEI CASHFLOW® 9500e* adapts to interface with all current gaming machine standards
- Bi-color diagnostic LED indicating operating and configuration status
- Easy-to-use iButton™ (touch memory) for configuration and configuration cloning
- Secure and fast coin updates with MEI CASHFLOW® programming module

ACCEPTANCE RATE

- 95% or greater coin acceptance***

VALIDATION

- 24-coin outputs available, increasing multiple currency and token options
- New coin-sensing technology, maximizing acceptance rate, combined with highest security
- Intelligent technology inside; automatic security algorithm and coin population adjustment

SHIPPING WEIGHT

9520e .5kg (1 lb.)
 9524e .8kg (1.75 lbs.)
 9528e .8kg (1.75 lbs.)

POWER

Full Operating voltage ranges:
 10V to 15VDC | 12V nominal

Current:

Idle: 120mA max
 Coin Flight: 160mA
 Accept Gate: 800mA
 2 Routing Solenoids: 2.3A - 320msec
 3 Routing Solenoids: 3A - 320msec

MEI CASHFLOW® 9500e PART NUMBERS

Part Number	Description
750001034	CF9520e USFC0001 (\$)
750009035	CF9528e EUTA8001 (€)
750003033	CF9520e GBTC0001 (£)
750005032	CF9524e GBTA4001 (£)
750007036	CF9524e GBTA4002 (£)

For other profiles, please contact your MEI sales associate.

Model Number Breakdown

GB T A 4 001 (£)

a	b	c	d	e	f
a Country	GB - Core profile				
	EU				
	US				
b Entry	T - Top entry				
	F - Front entry				
c Reject	A - Reject left 1				
	B - Reject left 2				
	C - Reject front				
d Way	0 - Way separation				
	4 - Way active separation				
	B - Way active separation				
e Profile	Profile designation				
f Currency	£ - British Pound				
	\$ - US Dollar				
	€ - Euro				

MEI LOCATIONS:

UNITED STATES

Corporate Headquarters
 1301 Wilson Drive
 West Chester, PA 19380
 Telephone: 1 610 430 2700
 Facsimile: 1 610 430 2694
 Customer Service: 1 800 345 8215
 Technical Support: 1 800 345 8172

Las Vegas, NV

Telephone: 1 702 873 4866
 Facsimile: 1 702 873 6401

UNITED KINGDOM

Telephone: +44 (0) 118 938 1100
 Facsimile: +44 (0) 118 938 1120

SWITZERLAND

Telephone: +41 (0) 22 884 0505
 Facsimile: +41 (0) 22 884 0504

AUSTRALIA

Telephone: +61 2 8875 7753
 Facsimile: +61 2 8875 7957

CANADA

Telephone: +1 905 492 0851
 Facsimile: +1 905 492 0853

JAPAN

Telephone: +81 3 3221 8466
 Facsimile: +81 3 3221 8465

SPAIN

Telephone: +34 91 749 7516
 Facsimile: +34 91 749 9356

FRANCE

Telephone: +33 (0) 1 57 32 30 23
 Facsimile: +33 (0) 1 55 69 56 10

GERMANY

Telephone: +49 695 007 0420
 Facsimile: +49 695 007 0421

ITALY

Telephone: +39 02 69633722
 Facsimile: +39 02 69633723